

	tip oken à	LES 68	LES 78	LES+ALU S4	LES/ALU S5	LES 46	TREND	UNISASH
 www.lesko.si info@lesko.si  04 510 50 50								
dimenzije	debelina lesa	68mm	78mm	68/78mm	68/78mm	46mm	68/78mm	68mm
material	noter	les	les	les	les	les	les	les + steklo
	zunaj	les	les	aluminij	aluminij	les	les (alu) + steklo	aluminij
tip stekla in toplotni faktor <small>(izračun U_w je narejen za referenčno enokrilno okno dimenzije 123×148cm iz lesa smreke in steklom s SuperSpacer termo distančnikom $\psi_i=0,033$) (Ar = plin Argon) (Kr = plin Kripton) rdeče = najprimernejše</small>	4/16/:4 Ar $U_g=1.1$	$U_w=1.23$		$U_w=1.23$ (68)	$U_w=1.23$ (68)	4/8/:4 plin Argon $U_g=1.7$	$U_w=1.23$ (68)	4:/24/4/24/:6 kaljena stekla plin Argon TGI distančnik $U_g=0.5$ $U_w=0.81$
	4/16/:4* Ar $U_g=1.0$	$U_w=1.16$		$U_w=1.16$ (68)	$U_w=1.16$ (68)		$U_w=1.16$ (68)	
	4/12/:4* Kr $U_g=0.9$	$U_w=1.09$		$U_w=1.09$ (68)	$U_w=1.09$ (68)		$U_w=1.09$ (68)	
	4:/12/4/12/:4 Ar $U_g=0.7$		$U_w=0.92$	$U_w=0.92$ (78)	$U_w=0.96$ (68)	ali	$U_w=0.92$ (78)	
	4:/14/4/14/:4 Ar $U_g=0.6$		$U_w=0.85$	$U_w=0.85$ (78)			$U_w=0.85$ (78)	
	4:/18/4/18/:4 Ar $U_g=0.5$				$U_w=0.78$ (78)	enojno steklo	$U_w=0.78$ (78)	
	4:/12/4/12/:4 Kr $U_g=0.5$		$U_w=0.78$	$U_w=0.78$ (78)				
4:/12/4/12/:4 Kr $U_g=0.4$		$U_w=0.72$	$U_w=0.72$ (78)	$U_w=0.72$ (78)				
načini odpiranja	brez odpiranja (FIX)	a	a	a	a	a	a	a
	enoosno (ODP. ali KIP)	a	a	a	a	a	a	a
	kombinirano (ODP+KIP)	a	a	a	a	a	a	a
	nagibno-drsno (PSK)	a	a	a	a	a	a	a
	dvižno-drsno (HS)	a	a	a	a	a	a	a
100% skrito okovje	Rotó NT Designo	opcija	opcija	Opcija	opcija	ni možno	opcija	serijsko
oblika profila	soft	a	a	a	a	a		
	stil	a	a	a	a	a		
	eksklusiv	a	a	a	a	a		
	monaco (samo znotraj)	a	a	a	a	a		
	ostrorobno (samo znotraj)	a	a	a	a	a	a	a